


UCFB 201 ... UCFB 210 FLANSCHLAGER, GUSSGEHÄUSE



	Abmessungen [mm]																Tragzahl [kN]		Gewicht [kg]		
	d[mm]		b		D	l	s		h		e	i	z	Bi	n	S Schraube	Lager	Gehäuse		dyn.C	stat.C0
UCFB 201	12	110	62	52	52	25,5	10	13	42	27	32	15,0	33,3	31,0	12,7	M8	UC 201	FB 201	12,8	6,7	0,64
UCFB 202	15	110	62	52	52	25,5	10	13	42	27	32	15,0	33,3	31,0	12,7	M8	UC 202	FB 202	12,8	6,7	0,64
UCFB 203	17	110	62	52	52	25,5	10	13	42	27	32	15,0	33,3	31,0	12,7	M8	UC 203	FB 203	12,8	6,7	0,64
UCFB 204	20	110	62	52	52	25,5	10	13	42	27	32	15,0	33,3	31,0	12,7	M8	UC 204	FB 204	12,8	6,7	0,64
UCFB 205	25	116	68	52	56	27,0	10	13	45	27	34	16,0	35,7	34,0	14,3	M8	UC 205	FB 205	14,0	7,9	0,68
UCFB 206	30	132	80	55	65	31,0	10	13	50	29	40	18,0	40,2	38,1	15,9	M8	UC 206	FB 206	19,5	11,3	0,92
UCFB 207	35	144	90	62	70	34,0	10	15	55	32	46	19,0	44,4	42,9	17,5	M8	UC 207	FB 207	25,7	15,4	1,30
UCFB 208	40	164	100	72	78	36,0	12	16	60	41	50	21,0	51,2	49,2	19,0	M10	UC 208	FB 208	32,0	17,8	1,80
UCFB 209	45	175	105	76	80	38,0	12	18	65	43	54	22,0	52,2	49,2	19,0	M10	UC 209	FB 209	32,7	20,2	2,00
UCFB 210	50	184	114	82	86	40,0	12	18	68	46	58	22,0	54,6	51,6	19,0	M10	UC 210	FB 210	35,1	23,1	2,30