



# FLANSCH FÜR KOLBENSTANGEN Typ RF DIN ISO 8132 RF ...



	DA	FEJs1	HBH13	KE	KK	NEh13	UPma	LE min	m	F nom.	[mm]
	H13	3		+0,4 bis +0			x				
	[mm]	[mm]	[mm]	[mm]	[-]	[mm]	[-]	[mm]	[kg]	[kN]	
RF 10	-	-	-	-	-	-	-	18	-	5,0	25
RF 12	11,0	40	4 x $\bar{\Delta}$ ? 6,6	6,8	M 12 x 1,25	17	56	18	0,30	8,0	32
RF 16	14,5	45	4 x $\bar{\Delta}$ ? 9,0	9,0	M 14 x 1,5	19	63	22	0,39	12,5	40
RF 20	14,5	54	6 x $\bar{\Delta}$ ? 9,0	9,0	M 16 x 1,5	23	72	27	0,60	20,0	50
RF 25	14,5	63	6 x $\bar{\Delta}$ ? 9,0	9,0	M 20 x 1,5	29	82	34	1,00	32,0	63
RF 32	17,5	78	6 x $\bar{\Delta}$ ? 11,0	11,0	M 27 x 2	37	100	42	1,90	50,0	80
RF 40	20,0	95	8 x $\bar{\Delta}$ ? 13,5	13,0	M 33 x 2	46	120	52	3,19	80,0	100
RF 50	26,0	120	8 x $\bar{\Delta}$ ? 17,5	17,5	M 42 x 2	57	150	64	6,20	125,0	125
RF 63	33,0	150	8 x $\bar{\Delta}$ ? 22,0	21,5	M 48 x 2	64	190	75	11,40	200,0	160
RF 80	40,0	180	8 x $\bar{\Delta}$ ? 26,0	25,5	M 64 x 3	86	230	90	33,00	320,0	200